

HIGHLANDER II WITH ENCLOSURE

VERTICAL PLATFORM LIFT ENCLOSURE KIT



Vertical Platform Lifts are required to be enclosed when they have a lifting height of 60" or above for commercial applications and/or when they penetrate a floor. The enclosure kit allows for an integrated solution instead of constructing a hoistway.



KEY AVAILABLE FEATURES:

- Choice of acrylic or steel panels
- Acrylic roof with ventilation system
- Steel frame with SealKor powder coat
- 6' 8" lower door and upper landing gate
- Through-bolt fastening system for enhanced rust protection

HIGHLANDER II WITH ENCLOSURE PRODUCT SPECIFICATIONS

WEIGHT CAPACITY	750 lb	SPEED	9.5 to 15 FPM
DRIVE	<ul style="list-style-type: none">- ACME screw- 90V 2/3 HP fully sealed DC gear motor	POWER	<ul style="list-style-type: none">- 120V AC- 15 AMP circuit breaker
PLATFORM SIZES	<ul style="list-style-type: none">- 36" x 60" clear platform with 42" guard panel- 42" x 60" clear platform with 42" guard panel	WARRANTY	3-year
CERTIFIED	<ul style="list-style-type: none">- ETL listed- CSA B44.1/ASME A17.5-2019- Safety standard ASME A18.1-2020- Rated commercial and residential	FEATURES	<ul style="list-style-type: none">- 4" x 5" constant pressure paddle control- Seal-Kor powder coat with stainless steel hardware for outdoor use
SAFETY FEATURES	<ul style="list-style-type: none">- 4-LED indicators in top cap- Emergency stop button in platform- Overspeed brake- Overload protection- Interlocks for doors/gates- Manual lowering tool	OPTIONS	<ul style="list-style-type: none">- 3-stop with 3-button control panel- 36" or 42" upper landing door with EMI interlock- Battery backup UPS system- Fire-rated doors- Grab bar in platform- Key lock in platform- Safety pan- Wired or wireless call/send control

